

# Zeal ZeSuper Superior 20W40& 50 SG/CD

## Multigrade Gasoline and Diesel Engine Oil



### Product Data Sheet

#### Product Description

Zeal ZeSuper Superior 20W40& 50 SG/CD series are formulated with high quality base stocks and balanced additive system to provide high level of engine protection and performance. It works harder than other conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise. This product meets the requirements of most car manufacturers and is suitable for standard services.

#### Features & Benefits

- Good engine cleanliness, due to improved detergency and dispersancy.
- Good wear protection and improved resistance to oxidation.
- Superior protection against viscosity and thermal breakdown.
- Superior sludge protection for greater engine reliability.
- Easier cold starting compared to mono-grade engine oils.

#### Specifications

Zeal ZeSuper Superior 20W40& 50 meets or exceeds following International and Builder specifications:

- API SG,SF, CD
- ACEA A2/B2

#### Application

Zeal ZeSuper Superior 20W40& 50 is suitable for use in following:

- Automotive gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Pleasure boats, motorcycles without wet clutch, etc.
- Moderate duty LPG vehicles.
- Naturally aspirated or turbo-charged indirect injection diesel engines.

#### Typical Characteristics

Zeal ZeSuper Superior 20W40& 50e	Test Method	Units	20W-40	20W-50
Product Code			Z MGP 014	Z MGP 015
Density @ 15 °C	ASTM D 4052	gm/cc	0.888	0.890
Viscosity @ 100 °C	ASTM D 445	cSt	14.30	20.4
Viscosity @ 40 °C	ASTM D 445	cSt	107	175
Viscosity Index	ASTM D 2270	-	137	136
Pour Point	ASTM D 97	°C	-30	-30
Flash Point (COC)	ASTM D 92	°C	230	236
Total Base Number	ASTM D 2896	mg KOH/g	6.0	6.0
Phosphorous	ASTM D 4951	% wt	0.070	0.070
CCS Viscosity	ASTM D 5293	cP	6020 @ -15 °C	6060 @ -15 °C

The above figures are typical of blends with normal production tolerance and do not constitute a specification.