

Zeal Zepace Ultimate 5W40 SL.CF

Fully Synthetic-High Performance Multigrade Petrol Engine Oil

PRODUCT DATA SHEET

Product Data Sheet

PRODUCT DESCRIPTION

Zeal zepace ultimate 5W40 SL/CF operators of heavy-duty truck and bus fleets equipped with latest emission designs, including those with EGR systems, as well as satisfying the needs of older engines. It may be used in naturally aspirated and turbocharged diesel and petrol engines, providing excellent protection even under the most severe conditions.

FEATURES & BENEFITS

- Outstanding oxidation & thermal stability reduces sludge deposits and keeps the engine cleaner.
- Excellent fuel economy, due to its superior flow and frictional properties compared to conventional diesel engine oils.
- Excellent dispersancy provides outstanding soot control in Exhaust Gas Recirculation (EGR) systems.
- Extended TBN reserves provide improved acid neutralization and corrosion protection, which helps in extending oil drain intervals.
- It delivers excellent viscosity control, outstanding protection against wear and exceptional versatility featuring one oil for all fleet with multiple engine makes.

SPECIFICATIONS

Zeal zepace ultimate 5W40 SL/CF **meets or exceeds following International and Builder specifications:**

- API SL, SJ, CF
- ACEA A3/B3
- MB Approval 229.1
- VW 505 00

TYPICAL CHARACTERISTICS

Zeal ZeTurbo Endurance	Test Method	Units	5W-40
Density @ 15 °C	ASTM D 4052	gm/cc	0.850
Viscosity @ 100 °C	ASTM D 445	cSt	14.30
Viscosity @ 40 °C	ASTM D 445	cSt	88.6
Viscosity Index	ASTM D 2270	-	168
Pour Point	ASTM D 97	°C	-39
Flash Point (COC)	ASTM D 92	°C	228
Total Base Number	ASTM D 2896	mg KOH/g	8.4
Sulfated Ash	ASTM D 874	% wt	1.1
CCS Viscosity	ASTM D 5293	cP	4650 @ -30 °C

The above figures are typical of blends with normal production tolerance and do not constitute a specif

For further information, please contact: sales@zeallubricants.com, Website: www.zeallubricants.com