

# Zeal Zesuper Protect 20W40 SF/CD

MULTIGRADE PETROL – SYNTHETIC ENGINE OIL

PRODUCT DATA SHEET



## PRODUCT DESCRIPTION

Zeal Zesuper Protect 20W40 SF/CD is an extra high performance, multi-grade engine oil specifically formulated for severe service high-speed diesel engines in marine applications. Its advanced chemistry provides outstanding performance in both modern, demanding low-emission diesel engines and older diesel engines operating on low or high sulphur distillate fuel.

## FEATURES & BENEFITS

- Improved fuel economy & easy cold starts due to good fluidity at low temperatures.
- Reduces power robbing friction across engine speeds and conditions
- High resistant oil film even at high engine operating temperatures.
- Excellent detergency and dispersancy, reduces sludge formation which improves engine cleanliness.
- Excellent oxidation & thermal stability, helps in extending oil drain intervals.
- Superior wear protection for greater engine reliability and performance.

## SPECIFICATIONS

Zeal Zesuper Protect 20W40 SF/CD meets or exceeds following International and Builder specifications:

- API SF,CD
- ACEA A2/B2

## APPLICATIONS

Zeal Zesuper Protect 20W40 SF/CD is suitable for use in,

- Automotive gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Moderate duty LPG vehicles.
- Naturally aspirated or turbo-charged indirect injection diesel engines

## TYPICAL PHYSICAL CHARACTERISTICS

Zeal Zesuper Protect	Test Method	Units	20W-40
Density @ 15 °C	ASTM D 4052	gm/cc	0.888
Viscosity @ 100 °C	ASTM D 445	cSt	15.6
Viscosity @ 40 °C	ASTM D 445	cSt	120
Viscosity Index	ASTM D 2270	-	137
CCS Viscosity	ASTM D 5293	Cp @ -15 °C	6020
Pour Point	ASTM D 97	°C	-30
Flash Point (COC)	ASTM D 92	°C	230
Total Base Number	ASTM D 2896	mg KOH/g	6.2
phosphorous	ASTM D874	% wt	0.078

*These characteristics are typical of current product methods whilst future production will confirm to Zeal lubricants specifications, variations in these physical characteristics may occur.*

## PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point or to be recycled. Do not discharge used or new oil into drains, soil or water.

## ADDITIONAL INFORMATION

Based on available information, this product is not expected to produce adverse effect on health when used for the Applications referred to above and the recommendations provided in safety data sheet are followed. guidance on health and safety is available on the appropriate material safety data sheet(MSDS) which can be obtained from [www.zeallubricants.com](http://www.zeallubricants.com)