

ZEAL ZETRANS 75W90 HD GL-5

Product Data Sheet

Product Description

Zeal zetrans 75W90 HD GL-5 of lubricants are high performance heavy duty gear oils, formulated from high quality base oils and an advanced additive system. These lubricants are designed for automotive heavyduty transmissions, axles and final drives. Moreover these oils are specially engineered for heavy-duty axles and final drives where extreme pressures and shock loadings are expected.

Features & Benefits

- Exceptional thermal & oxidation stability protects against deposit formation and oil thickening, thus maintains the life and performance of lubricant and transmission.
- Outstanding anti-wear properties and excellent film strength provides exceptional equipment protection, that not only results in fewer breakdowns but also helps improve transmission efficiency.
- Excellent rust and corrosion protection for longer component life.
- Compatibility with seals and gaskets, leads to minimize oil leakage and reduced contamination.

Specifications

Zeal zetrans 75W90 HD GL-5 **meets or exceeds following International and Builder specifications:**

- API GL-5
- MIL-L-2105D (U.S Military Specification)
- MAN 342 M2
- ZF TE ML 05A, 7A, 12E, 16B, C & D, 17B, 19B, 21A

Application

Zeal zetrans 75W90 HD GL-5 are suitable for use in all Passenger cars, On-highway light and heavy duty trucks, and commercial vehicles.

- Suitable for Heavy duty manual transmissions, axles and final drives requiring API GL-5 level performance.
- Applications like Off-highway industries including: construction, mining, quarrying, and agriculture.
- Other heavy-duty industrial and automotive applications, involving hypoid gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque exists.

Typical Characteristics

Zeal zetrans HD	Test Method	Units	75W90
Density @ 15 °C	ASTM D 4052	gm/cc	0.890
Viscosity @ 40 °C	ASTM D 445	cSt	126.1
Viscosity @ 100 °C	ASTM D 445	cSt	17.4
Viscosity Index	ASTM D 2270	-	152
Pour Point	ASTM D 97	°C	-24
Flash Point (COC)	ASTM D 92	°C	236
Copper Strip Corrosion	ASTM D 130	-	1B
Foam Seq I,II,III	ASTM D 892	ml/ml	10/0
Phosphorus	ASTM D 4951	%wt	0.055

The above figures are typical of blends with normal production tolerance and do not constitute a specification.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point or to be recycled. Do not discharge used or new oil into drains, soil or water.

ADDITIONAL INFORMATION

Based on available information, this product is not expected to produce adverse effect on health when used for the Applications referred to above and the recommendations provided in safety data sheet are followed. guidance on health and safety is available on the appropriate material safety data sheet(MSDS) which can be obtained from www.zeallubricants.com