

Zeal Zepace Premium 4T 25W60 SL JASO MA2

4-STROKE ENGINE OIL

PRODUCT DATA SHEET



PRODUCT DESCRIPTION

Zeal Zepace Premium 4T 25W60 SL JASO MA2 is a high performance 4-stroke motorcycle oil specially made from high quality base oils and superior additives to retain its viscosity during use which provides uniform lubrication to vital engine parts. It guarantees piston ring sealing and reduces deposits: low volatility, lower oil consumption, prevents loss of compression, maintain engine power.

FEATURES & BENEFITS

- Improved fuel economy & easy cold starts due to good fluidity at low temperatures.
- Limits the appearance of foam on the surface of engine parts
- High resistant oil film even at high engine operating temperatures.
- Excellent detergency and dispersancy, reduces sludge formation which improves engine cleanliness.
- Excellent oxidation & thermal stability, helps in extending oil drain intervals.
- Superior wear protection for greater engine reliability and performance.
- Ideal performance in extreme pressure conditions

SPECIFICATIONS

Zeal Zepace Premium 4T 25W60 SL JASO MA2 **meets or exceeds following International and Builder specifications:**

- API SL, SJ, CF
- JASO MA2
- VW 505 00

APPLICATIONS

Zeal Zepace Premium 4T 25W60 SL JASO MA2 is suitable for use in,

- used in all 4 stroke bikes as recommended by manufacturer's manual
- For use in on/off road 4 stroke motorcycles and ATVs
- Meets API SL and JASO MA2 services
- Resists breakdown in the most severe engine environments.

TYPICAL PHYSICAL CHARACTERISTICS

Zeal Zespace Premium	Test Method	Units	25W-60
Density @ 15 °C	ASTM D 4052	gm/cc	0.872
Viscosity @ 100 °C	ASTM D 445	cSt	17.86
Viscosity @ 40 °C	ASTM D 445	cSt	146.6
Viscosity Index	ASTM D 2270	-	135
CCS Viscosity	ASTM D 5293	Cp @ -15 °C	5126
Pour Point	ASTM D 97	°C	-21
Flash Point (COC)	ASTM D 92	°C	230
Total Base Number	ASTM D 2896	mg KOH/g	7.8

These characteristics are typical of current product methods whilst future production will confirm to Zeal lubricants specifications, variations in these physical characteristics may occur.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point or to be recycled. Do not discharge used or new oil into drains, soil or water.

ADDITIONAL INFORMATION

Based on available information, this product is not expected to produce adverse effect on health when used for the Applications referred to above and the recommendations provided in safety data sheet are followed. guidance on health and safety is available on the appropriate material safety data sheet(MSDS) which can be obtained from www.zeallubricants.com